

MULTIDISC

76

Anbaurahmen Front Telaio attacco frontale Frame front mounting

DE


- » Drehbare Gummiräder höhenverstellbar in 5 Positionen
- » Schnitthöhe einstellbar in 5 Positionen von 5cm - 13cm.
- » Hydraulische Transporteinstellung der Außenrahmen
- » Verschiebbare gepolsterte Mähköpfe mit Hydraulikmotor
- » Hydraulischer Antrieb
- » CE-Unfallschutz

IT

- » Ruote pneumatiche pivotanti regolabili in 5 posizioni
- » Altezza di taglio regolabile in 5 posizioni da 5cm a 13cm
- » Posizionamento idraulico dei telai esterni per il trasporto
- » Le testate singole si lasciano spostare lateralmente e sono ammortizzate tramite molle.
- » Trasmissione idraulica
- » Protezione antiinfortunistica CE

EN

- » Mobile pneumatic wheels adjustable in 5 positions
- » Adjustable cutting height in 5 positions from 5cm to 13cm
- » Hydraulic positioning of external cutting heads for transport
- » Cutting heads are displaceable and are relieved by springs
- » Hydraulic transmission
- » CE accident protection

Mod.	Messer Lame Blades			 Außenabmaße Ingombri esterni					Schnittbreite Larghezza di taglio Cutting width		
		HP	KG	A	B	C	D	E	A	/	B
MULTIDISC 35/45/500	5	40 - 80	700	260	175	100	25	445	35	/	45

2 Aussenrahmen
2 Testata esterna
2 external heads

3 zentrale Rahmen
3 testata centrali
3 central heads